AERIAL PERSONNEL LIFTS START UP AND PRE-SHIFT INSPECTION PROCEDURES

Before using the PERSONNEL LIFT for the first time every day, a pre-shift inspection must be conducted and a written checklist must be submitted to your supervisor.

	Date:	
Inspection Completed I	By:	
✓ = Satisfactory	X = Requires Service or Closer Inspection	N/A = Does Not Apply
Check for Lockout o	or Tagout. If a tag or lock is present, do not	t operate the equipment
Check that the key w		
	sconnect and switch to the off position	
	any leaks, particularly in the area where the	e machine has been parked
	cylinder leaks, damaged hydraulic hoses ar	
Check hydraulic flui	d level	-
Check brake fluid le	vel	
Check engine oil lev		
Check transmission	fluid level	
Check battery fluid l	evels	
	tires for low pressure, tire wear and damag	
	ensure that all buttons move freely. Be sure	
	ontrols are properly labeled and all functio	ons are easily identified
Check outrigger legs		
	her (Make sure it is fully charged)	
	f operator compartment and kick plate	
Check that battery is	fully charged or fuel system is full	
	E "ON" POSITION AND CONTINUE O OPERATIONAL CHECKL	
Refore conducting of	perational checks, make sure that the fall z	
	trol buttons function as labeled	one is clear
Control restraint is in	n safe condition. Check for bare wires and	loose connections
Test outrigger legs for		
Test lights for proper	*	
	ing or grabbing or complete failure	
Test horn for proper	function	
Test steering in both	directions	
	ounds or vibrations while traveling or braki	ing
Test steering in both		
Make sure that all sa	• •	
Make sure you have	proper fall arrest equipment and it is in go	od working condition
	UIPMENT MUST BE INSPECTED EVERY SET ASIDE ANY QUESTIONABLE FALI <u>"DO NOT USE IT"</u>	