

CONVERSION KIT SM-1 STANDARD ECONOMY SERIES TO MARS

This instruction set is intended for those converting a rear load changer from the Coinco Mag series to the Mars AE series validators.

INSTALLATION

Begin by turning off the power to the changer. Remove the original validator (retain the 4 nuts) and set aside.

If you also purchased the VALLEY PRIDE security plate (item FACE COVER SS) install the plate over the existing studs and attach using the 4 previously removed nuts. Attach the new Mars validator to the studs on the security plate and using the supplied nuts tighten into place. NOTE: The "mask" of the Mars has been specially modified to allow the use of the security plate.

If you did not purchase the security plate simply replace the existing validator with the new Mars unit and then using the 4 removed nuts simply tighten into place.

WIRING AND TESTING

The wiring harness of the Mars will simply plug into the existing harness. Insert several bills to test for proper operation. Your unit has been programmed via a programming coupon. If you desire different acceptance values, you may make a copy of the blank coupon found in the Mars instruction manual. Fill in the blanks and complete the new program. Complete programming information can be found in the Mars booklet.

It is very important that the pulse, pulses per dollar and interface selection portion of the programming coupon remain as originally programmed.

DO NOT CHANGE THE DIP SWITCH SETTINGS!!! THESE MUST BE LEFT IN THE OFF POSITION.

NOTES:

- The Billbox must be in place before the unit will accept bills.
- The red light at the rear of the validator will burn steady. If the light flashes in a pattern of two flashes check the controller and/or change level. The 2 flash pattern indicates a problem with the changer itself.....not with the validator.