

Intake - 1978 and 1979 models

Measured clearance	Installed pad number																								
	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320
0.00 ~ 0.05				200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305
0.06 ~ 0.10			200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310
0.11 ~ 0.15		200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315
0.16 ~ 0.20																									
0.21 ~ 0.25	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	
0.26 ~ 0.30	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320		
0.31 ~ 0.35	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320			
0.36 ~ 0.40	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320				
0.41 ~ 0.45	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320					
0.46 ~ 0.50	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320						
0.51 ~ 0.55	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320							
0.56 ~ 0.60	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320								
0.61 ~ 0.65	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320									
0.66 ~ 0.70	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320										
0.71 ~ 0.75	255	260	265	270	275	280	285	290	295	300	305	310	315	320											
0.76 ~ 0.80	260	265	270	275	280	285	290	295	300	305	310	315	320												
0.81 ~ 0.85	265	270	275	280	285	290	295	300	305	310	315	320													
0.86 ~ 0.90	270	275	280	285	290	295	300	305	310	315	320														
0.91 ~ 0.95	275	280	285	290	295	300	305	310	315	320															
0.96 ~ 1.00	280	285	290	295	300	305	310	315	320																
1.01 ~ 1.05	285	290	295	300	305	310	315	320																	
1.06 ~ 1.10	290	295	300	305	310	315	320																		
1.11 ~ 1.15	295	300	305	310	315	320																			
1.16 ~ 1.20	300	305	310	315	320																				
1.21 ~ 1.25	305	310	315	320																					
1.26 ~ 1.30	310	315	320																						
1.31 ~ 1.35	315	320																							
1.36 ~ 1.40	320																								

VALVE CLEARANCE (engine cold) 0.16~0.20 mm

Example: Installed is 250

Measured clearance is 0.32 mm

Replace 250 pad with 265

*Pad number: (example) Pad No. 250 = 2.50 mm

Pad No. 255 = 2.55 mm

Always install pad with number down

Exhaust - 1978 and 1979 models

Measured clearance	Installed pad number																								
	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320
0.00 ~ 0.05					200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300
0.06 ~ 0.10				200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305
0.11 ~ 0.15			200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310
0.16 ~ 0.20	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	
0.21 ~ 0.25																									
0.26 ~ 0.30	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	
0.31 ~ 0.35	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320		
0.36 ~ 0.40	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320			
0.41 ~ 0.45	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320				
0.46 ~ 0.50	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320					
0.51 ~ 0.55	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320						
0.56 ~ 0.60	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320							
0.61 ~ 0.65	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320								
0.66 ~ 0.70	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320									
0.71 ~ 0.75	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320										
0.76 ~ 0.80	255	260	265	270	275	280	285	290	295	300	305	310	315	320											
0.81 ~ 0.85	260	265	270	275	280	285	290	295	300	305	310	315	320												
0.86 ~ 0.90	265	270	275	280	285	290	295	300	305	310	315	320													
0.91 ~ 0.95	270	275	280	285	290	295	300	305	310	315	320														
0.96 ~ 1.00	275	280	285	290	295	300	305	310	315	320															
1.01 ~ 1.05	280	285	290	295	300	305	310	315	320																
1.06 ~ 1.10	285	290	295	300	305	310	315	320																	
1.11 ~ 1.15	290	295	300	305	310	315	320																		
1.16 ~ 1.20	295	300	305	310	315	320																			
1.21 ~ 1.25	300	305	310	315	320																				
1.26 ~ 1.30	305	310	315	320																					
1.31 ~ 1.35	310	315	320																						
1.36 ~ 1.40	315	320																							
1.41 ~ 1.45	320																								

VALVE CLEARANCE (engine cold) 0.21~0.25 mm

Example: Installed is 250

Measured clearance is 0.32 mm

Replace 250 pad with 260

*Pad number: (example) Pad No. 250 = 2.50 mm

Pad No. 255 = 2.55 mm

Always install pad with number down